

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | XND5566SL          |          |
| 光源      | LED3000_80_5165 ×1 | 5165.0lm |
| 管理番号    | K0179571(0)DB1     |          |
| BZ分類    | BZ1                |          |

| 器具効率   | 100%            | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|-----------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |                 |         | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束   | 0%              | 壁       |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 下方光束   | 100%            | 床       | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
|        |                 | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良               | 0.76    | 0.6           | 79  | 71  | 67  | 63  | 78  | 71  | 66  | 63  | 76  | 70  | 66  | 63  | 75  | 69  | 66  | 63  | 62 |
|        | 中               | 0.72    | 0.8           | 86  | 80  | 76  | 72  | 85  | 79  | 75  | 72  | 84  | 79  | 75  | 72  | 82  | 78  | 74  | 72  | 70 |
|        | 否               | 0.64    | 1.0           | 91  | 85  | 81  | 78  | 90  | 85  | 81  | 78  | 88  | 84  | 80  | 78  | 86  | 83  | 80  | 77  | 76 |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 95            | 90  | 86  | 83  | 94  | 89  | 86  | 83  | 92  | 88  | 85  | 82  | 90  | 87  | 84  | 82  | 80  |    |
|        |                 | 1.5     | 97            | 93  | 89  | 87  | 96  | 92  | 89  | 86  | 94  | 91  | 88  | 86  | 92  | 89  | 87  | 85  | 83  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 100           | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87  |    |
|        |                 | 2.5     | 102           | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 99  | 96  | 94  | 93  | 97  | 95  | 93  | 92  | 90  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0           | 103 | 100 | 98  | 96  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95  | 93  | 91 |
|        | 横方向 (A)         | 縦方向 (B) | 4.0           | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
| Hm     | 0.70Hm          | 0.70Hm  | 5.0           | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97  | 95 |
|        |                 |         | 7.0           | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 99  | 96 |
|        |                 |         | 10.0          | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 97 |

