

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND7539SV                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_80_6910 x1 6910.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0179814(0)DB1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

| 器具効率   | 100%    | 天井      | 80%  |                  |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |    |
|--------|---------|---------|------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
|        |         |         | 壁    | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |    |
| 上方光束   | 0%      | 反射率     | 床    | 10%              |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |    |
| 下方光束   | 100%    |         | 室指数  | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
| 保守率    | 良       | 0.76    | 0.6  | 77               | 70  | 65  | 62  | 76  | 69  | 65  | 62  | 75  | 69  | 64  | 61  | 73  | 68  | 64  | 61  | 60 |    |
|        | 中       | 0.72    | 0.8  | 86               | 79  | 75  | 71  | 85  | 79  | 74  | 71  | 83  | 78  | 74  | 71  | 81  | 77  | 73  | 71  | 69 |    |
|        | 否       | 0.64    | 1.0  | 91               | 85  | 81  | 78  | 90  | 84  | 80  | 77  | 88  | 83  | 80  | 77  | 86  | 82  | 79  | 77  | 75 |    |
|        |         |         |      | 1.25             | 94  | 89  | 86  | 83  | 93  | 89  | 85  | 83  | 91  | 88  | 85  | 82  | 90  | 86  | 84  | 82 | 80 |
| 下方投影面積 |         |         | 1.5  | 97               | 92  | 89  | 86  | 96  | 92  | 89  | 86  | 94  | 90  | 88  | 85  | 92  | 89  | 87  | 85  | 83 |    |
| 等価発光面積 |         |         | 2.0  | 100              | 96  | 93  | 91  | 99  | 95  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |    |
| 取付高さ   | 器具間隔最大限 |         | 2.5  | 102              | 99  | 96  | 94  | 100 | 98  | 96  | 94  | 98  | 96  | 94  | 93  | 96  | 95  | 93  | 92  | 90 |    |
|        | 横方向 (A) | 縦方向 (B) | 3.0  | 103              | 100 | 98  | 96  | 102 | 99  | 97  | 96  | 99  | 98  | 96  | 94  | 98  | 96  | 95  | 93  | 91 |    |
| Hm     | 1.13Hm  | 1.13Hm  | 4.0  | 104              | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 97  | 96  | 93 |    |
|        |         |         | 5.0  | 105              | 103 | 102 | 101 | 104 | 102 | 101 | 100 | 102 | 101 | 99  | 98  | 100 | 99  | 98  | 97  | 95 |    |
|        |         |         | 7.0  | 106              | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 99  | 96 |    |
|        |         |         | 10.0 | 107              | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 97 |    |

