

# 屋内照明器具特性

品番 (品名)	XND3596SL		
光源	LED3000_80_3900 ×1	3900.0 1m	
管理番号	K0179667(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		室指数	照明率 ( X0.01 )																ZCM
保守率	良 0.76	0.6	73	65	59	55	72	64	59	55	70	63	59	55	69	63	58	55	54	
	中 0.72	0.8	82	74	69	65	81	74	69	65	79	72	68	65	77	72	68	64	63	
	否 0.64	1.0	87	80	75	72	86	80	75	71	84	78	74	71	82	77	74	71	69	
下方投影面積	cm <sup>2</sup>	1.25	91	85	81	78	90	85	81	77	88	83	80	77	86	82	79	76	75	
		1.5	94	89	85	82	93	88	85	81	91	87	84	81	89	85	83	80	78	
等価発光面積	cm <sup>2</sup>	2.0	98	94	90	87	97	93	90	87	95	91	89	86	93	90	87	85	83	
		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	87	
取付高さ	器具間隔最大限		3.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	92	91	89
	横方向 (A)	縦方向 (B)	4.0	103	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94	91
Hm	0.73Hm	0.73Hm	5.0	105	103	101	99	103	102	100	98	101	100	98	97	99	98	97	96	93
			7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95
			10.0	107	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	96

