

# 屋内照明器具特性

品番 (品名)	NTN88081B				
光源	LLD2000LCE1	×1	531.0	lm	
管理番号	K0179237(0)DR1				
BZ分類	BZ5				

器具効率	98%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	94%		室指数	照明率 (×0.01)																ZCM
保守率	良	0.69	0.6	55	43	35	30	53	42	35	29	50	40	34	29	48	39	33	29	27
	中	0.67	0.8	64	53	45	40	63	52	45	39	59	50	44	39	56	49	43	38	36
	否	0.63	1.0	71	60	52	47	69	59	52	46	65	57	51	46	62	55	49	45	42
			1.25	77	67	60	54	75	66	59	54	71	63	57	53	68	61	56	52	49
下方投影面積			1.5	81	72	65	59	79	70	64	59	75	68	62	58	71	66	61	57	54
等価発光面積			2.0	86	79	73	68	84	77	72	67	80	75	70	66	77	72	68	64	61
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	77	72	84	79	75	71	80	76	73	69	66
	横方向 (A)	縦方向 (B)	3.0	92	86	82	77	90	85	80	77	86	82	78	75	83	79	76	73	70
Hm	1.26Hm	1.26Hm	4.0	95	91	87	83	93	89	85	82	90	86	83	80	86	83	81	78	75
			5.0	97	93	90	87	95	92	89	86	92	89	86	84	88	86	84	82	78
			7.0	99	96	94	91	97	95	92	90	94	92	90	88	91	89	87	86	82
			10.0	101	99	97	95	99	97	95	94	96	94	93	91	93	91	90	89	85

