

# 屋内照明器具特性

品番 (品名)	NTN88081B		
光源	LLD3020LCB1 ×1	795.0 1m	
管理番号	K0179242(0)DR1		
BZ分類	BZ1		

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 2%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.69	0.6	80	74	70	67	79	74	70	67	78	73	69	67	77	72	69	67	65	
	中 0.67		0.8	86	80	76	73	85	80	76	73	83	79	75	73	82	78	75	73	71
	否 0.63		1.0	90	84	81	78	89	84	80	77	87	82	79	77	85	81	79	76	75
下方投影面積	cm <sup>2</sup>	1.25	93	88	84	82	91	87	84	81	89	86	83	81	87	84	82	80	78	
		1.5	95	90	87	84	93	90	86	84	91	88	85	83	89	86	84	82	81	
等価発光面積	cm <sup>2</sup>	2.0	97	94	91	88	96	93	90	88	94	91	89	87	92	89	87	86	84	
		2.5	99	96	93	91	98	95	92	90	95	93	91	89	93	91	89	88	86	
取付高さ	器具間隔最大限		3.0	100	97	95	93	99	96	94	92	96	94	92	91	94	92	91	90	87
	横方向 (A)	縦方向 (B)	4.0	101	99	97	96	100	98	96	95	98	96	95	93	95	94	93	92	89
Hm	0.42Hm	0.42Hm	5.0	102	100	99	97	101	99	98	96	98	97	96	95	96	95	94	93	90
			7.0	103	102	101	99	102	101	100	98	99	98	97	97	96	95	95	92	
			10.0	104	103	102	101	103	102	101	100	100	99	99	98	98	97	97	96	93

