

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XND5 5 3 6 S N     |           |
| 光源      | LED5000_80_5365 ×1 | 5365.0 lm |
| 管理番号    | K0179575 (0) DB 1  |           |
| BZ分類    | BZ1                |           |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率             | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|                  | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束             | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 室指数              | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率              | 良               | 0.76    | 0.6  | 87  | 82  | 78  | 76  | 86  | 81  | 78  | 76  | 85  | 81  | 78  | 76  | 84  | 80  | 77  | 75  | 74  |
|                  | 中               | 0.72    | 0.8  | 92  | 88  | 84  | 82  | 92  | 87  | 84  | 82  | 90  | 86  | 84  | 82  | 89  | 86  | 83  | 81  | 80  |
|                  | 否               | 0.64    | 1.0  | 96  | 92  | 89  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 88  | 86  | 92  | 89  | 87  | 85  | 84  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 98   | 95  | 92  | 90  | 98  | 94  | 92  | 90  | 96  | 93  | 91  | 89  | 94  | 92  | 90  | 89  | 87  |     |
|                  |                 | 1.5     | 100  | 97  | 94  | 92  | 99  | 96  | 94  | 92  | 97  | 95  | 93  | 91  | 96  | 94  | 92  | 91  | 89  |     |
| 取付高さ             | 器具間隔最大限         |         | 2.5  | 104 | 101 | 99  | 98  | 103 | 100 | 99  | 97  | 101 | 99  | 97  | 96  | 99  | 97  | 96  | 95  | 93  |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0  | 104 | 102 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 100 | 98  | 97  | 96  | 94  |
| Hm               | 0.81Hm          | 0.81Hm  | 4.0  | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 99  | 98  | 96  |
|                  |                 |         | 5.0  | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 99  | 97  |
|                  |                 |         | 7.0  | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 102 | 101 | 100 | 100 | 99  | 97  |
|                  |                 |         | 10.0 | 107 | 107 | 106 | 105 | 106 | 106 | 105 | 104 | 104 | 104 | 103 | 103 | 102 | 101 | 101 | 101 | 98  |

