

屋内照明器具特性

品番 (品名)	NNN15510															
光源	LED5000_70_2730 x1 2730.0 lm															
管理番号	K0167806(0)DR1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	43%	室指数	照明率 (X0.01)																ZCM		
下方光束	57%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	48	35	28	22	44	33	26	21	37	29	23	19	31	24	20	16	11		
		0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16		
		1.0	62	51	43	37	58	48	40	35	49	41	35	31	41	35	30	27	19		
		1.25	68	57	49	43	63	53	46	41	54	46	41	36	45	39	35	31	23		
下方投影面積	c m ²	1.5	72	62	54	48	67	58	51	46	57	50	45	40	48	43	38	35	26		
		2.0	77	69	62	56	72	64	58	53	62	56	51	47	52	48	44	40	30		
取付高さ	器具間隔最大限		2.5	81	73	67	62	75	69	63	58	65	60	55	51	55	51	47	44	33	
	横方向 (A)	縦方向 (B)	3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36	
1.5m	1.99m	2.14m	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40	
2	2.63	2.7	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42	
2.5	3.27	3.27	7.0	91	88	84	81	86	82	79	77	74	72	70	67	64	62	60	58	45	
3	3.91	3.87	10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48	

