

# 屋内照明器具特性

品番 (品名)	NNN15512														
光源	LED3500_70_2645 x1 2645.0 1 m														
管理番号	K0167806(0)DR1														
BZ分類	BZ7/0.7/BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
		床	10%				10%				10%				10%				0%			
上方光束	43%	室指数																				
下方光束	57%	照明率 ( X0.01)																				
		ZCM																				
保守率	良 中 否	0.63	0.6	0.56	0.6	48	35	28	22	44	33	26	21	37	29	23	19	31	24	20	16	11
		0.6	0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16		
		0.56	1.0	62	51	43	37	58	48	40	35	49	41	35	31	41	35	30	27	19		
			1.25	68	57	49	43	63	53	46	41	54	46	41	36	45	39	35	31	23		
下方投影面積	c m <sup>2</sup>	1.5	72	62	54	48	67	58	51	46	57	50	45	40	48	43	38	35	26			
		2.0	77	69	62	56	72	64	58	53	62	56	51	47	52	48	44	40	30			
取付高さ	器具間隔最大限		2.5	81	73	67	62	75	69	63	58	65	60	55	51	55	51	47	44	33		
	横方向 (A)	縦方向 (B)																				
1.5m	1.99 m	2.14 m	3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36		
2	2.63	2.7	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40		
2.5	3.27	3.27	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42		
3	3.91	3.87	7.0	91	88	84	81	86	82	79	77	74	72	70	67	64	62	60	58	45		
			10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48		

