

屋内照明器具特性	
品番 (品名)	LGC65827
光源	LED6500_70_5540 x1 5540.0 lm
管理番号	K0182159(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	12%	床	10%				10%				10%				10%				0%				
下方光束	88%	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.4	4.1	3.3	2.8	5.2	4.0	3.3	2.7	4.8	3.8	3.1	2.7	4.5	3.6	3.0	2.6	2.3			
	中	0.6	0.8	6.3	5.1	4.3	3.7	6.1	5.0	4.2	3.7	5.7	4.7	4.1	3.6	5.3	4.5	3.9	3.5	3.1			
	否	0.56	1.0	6.9	5.8	5.0	4.4	6.7	5.7	4.9	4.3	6.2	5.4	4.7	4.2	5.8	5.1	4.5	4.1	3.7			
			1.25	7.5	6.5	5.7	5.1	7.3	6.3	5.6	5.0	6.8	6.0	5.4	4.9	6.3	5.7	5.1	4.7	4.3			
下方投影面積		cm <sup>2</sup>	1.5	7.9	7.0	6.2	5.7	7.7	6.8	6.1	5.6	7.2	6.4	5.8	5.4	6.7	6.1	5.6	5.2	4.8			
等価発光面積		cm <sup>2</sup>	2.0	8.5	7.7	7.0	6.5	8.2	7.5	6.9	6.4	7.7	7.1	6.6	6.1	7.2	6.7	6.3	5.9	5.4			
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.1	7.5	7.1	6.6	7.6	7.1	6.7	6.4	5.9			
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.5	8.8	8.3	7.8	7.3	8.3	7.8	7.4	7.0	7.8	7.4	7.1	6.8	6.3			
1.5m	1.92m	1.92m	4.0	9.4	8.9	8.5	8.1	9.2	8.7	8.3	7.9	8.6	8.3	7.9	7.6	8.2	7.8	7.5	7.3	6.7			
2	2.53	2.53	5.0	9.6	9.2	8.8	8.5	9.4	9.0	8.6	8.3	8.8	8.5	8.2	8.0	8.4	8.1	7.9	7.6	7.1			
2.5	3.15	3.15	7.0	9.9	9.5	9.2	9.0	9.6	9.3	9.0	8.8	9.1	8.9	8.6	8.4	8.6	8.4	8.2	8.0	7.5			
3	3.78	3.78	10.0	10.1	9.8	9.6	9.4	9.8	9.6	9.4	9.2	9.3	9.1	8.9	8.8	8.8	8.7	8.5	8.4	7.8			

