

屋内照明器具特性	
品番 (品名)	LGC45825
光源	LED6500_70_4430 x1 4430.0 1m
管理番号	K0182161(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	5%	床	10%				10%				10%				10%				0%				
下方光束	95%	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.6	4.3	3.6	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	3.0	4.9	4.0	3.4	2.9	2.7			
	中	0.6	0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.9	3.6			
	否	0.56	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.3	4.7	6.6	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.3			
			1.25	7.8	6.8	6.0	5.5	7.6	6.7	6.0	5.4	7.2	6.4	5.8	5.3	6.8	6.2	5.7	5.2	4.9			
下方投影面積	c m <sup>2</sup>		1.5	8.2	7.3	6.6	6.0	8.0	7.1	6.5	6.0	7.6	6.9	6.3	5.8	7.2	6.6	6.1	5.7	5.4			
	等価発光面積		c m <sup>2</sup>	2.0	8.7	8.0	7.4	6.8	8.5	7.8	7.3	6.8	8.1	7.5	7.0	6.6	7.8	7.3	6.8	6.5	6.1		
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.9	7.4	8.9	8.3	7.8	7.3	8.5	8.0	7.5	7.2	8.1	7.7	7.3	7.0	6.6			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.8	8.3	7.8	9.1	8.6	8.1	7.7	8.7	8.3	7.9	7.5	8.4	8.0	7.7	7.4	7.0			
1.5m	1.93m	1.92m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.6	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.5			
2	2.54	2.53	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.4	8.9	8.7	8.4	8.2	7.8			
2.5	3.17	3.15	7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.2			
3	3.77	3.76	10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.5	9.4	9.2	9.4	9.2	9.1	9.0	8.5			

