

# 屋内照明器具特性

品番 (品名)	LGC55123														
光源	LED6500_70_5100 x1 5100.0 lm														
管理番号	K0182143(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	11%	室指数																		
下方光束	89%	照明率 ( X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.3	3.6	3.0	5.4	4.2	3.5	3.0	5.0	4.1	3.4	2.9	4.7	3.9	3.3	2.9	2.6	
		0.8	6.5	5.4	4.6	4.0	6.3	5.3	4.5	4.0	5.9	5.0	4.4	3.9	5.6	4.8	4.2	3.8	3.5	
		1.0	7.2	6.1	5.3	4.8	6.9	6.0	5.3	4.7	6.5	5.7	5.1	4.6	6.1	5.4	4.9	4.5	4.1	
		1.25	7.8	6.8	6.1	5.5	7.5	6.6	6.0	5.4	7.1	6.3	5.7	5.3	6.6	6.0	5.5	5.1	4.8	
下方投影面積	c m <sup>2</sup>	1.5	8.2	7.3	6.6	6.1	7.9	7.1	6.5	6.0	7.4	6.8	6.2	5.8	7.0	6.5	6.0	5.6	5.2	
		2.0	8.7	8.0	7.4	6.9	8.5	7.8	7.2	6.8	8.0	7.4	6.9	6.5	7.5	7.1	6.7	6.3	5.9	
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.9	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.1	7.9	7.5	7.1	6.8	6.4
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.7	8.6	8.1	7.8	7.4	8.1	7.8	7.5	7.2	6.7
1.5m	1.95m	1.93m	4.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	8.9	8.5	8.2	8.0	8.4	8.2	7.9	7.7	7.2
2	2.55	2.53	5.0	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.1	8.8	8.5	8.3	8.6	8.4	8.2	8.0	7.5
2.5	3.16	3.14	7.0	10.0	9.7	9.5	9.2	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.9	8.7	8.5	8.4	7.8
3	3.79	3.76	10.0	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.5	9.3	9.2	9.0	9.0	8.9	8.8	8.7	8.1

