

屋内照明器具特性

品番 (品名)	NND26788K									
光源	LED6000_70_180 x1					180.0 lm				
管理番号	K0178214 (1) DB1									
BZ分類	BZ4/0.7/BZ3/3.5/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%																					
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																				
上方光束	1%	反射率	床		10%		10%		10%		10%		10%		10%		0%																							
下方光束	99%		室指数																																					
		照明率 (X0.01)																	ZCM																					
保守率	良	0.69	0.6	62	50	43	38	60	50	43	38	58	49	43	38	56	48	42	38	36																				
	中	0.67	0.8	72	61	54	49	70	61	54	49	68	59	53	49	65	58	53	49	47																				
	否	0.63	1.0	78	69	62	57	77	68	62	57	74	66	61	56	71	65	60	56	54																				
			1.25	84	75	69	64	82	75	69	64	79	73	68	63	77	71	67	63	61																				
下方投影面積			cm ²		1.5		87		80		74		69		86		79		74		69		83		77		72		68		80		75		71		68		66	
等価発光面積			cm ²		2.0		92		86		81		77		91		85		80		77		88		83		79		76		85		81		78		75		72	
取付高さ	器具間隔最大限		2.5		95		90		86		82		94		89		85		81		91		87		83		80		88		85		82		79		77			
	横方向 (A)	縦方向 (B)	3.0		97		93		89		86		96		92		88		85		93		90		87		84		91		88		85		83		80			
Hm	1.25Hm	1.25Hm	4.0		100		96		93		90		99		95		92		90		96		93		91		88		93		91		89		87		84			
			5.0		102		99		96		93		100		97		95		93		98		95		93		91		95		93		91		90		87			
			7.0		103		101		99		97		102		100		98		96		99		98		96		95		97		95		94		93		90			
			10.0		105		103		102		100		103		102		101		99		101		100		98		97		98		97		96		95		92			

