

# 屋内照明器具特性

品番 (品名)	LGBZ8116									
光源	LED2700_70_4440 x1 4440.0 lm									
管理番号	K0181528(0)DB1									
BZ分類	BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		18%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		82%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 ) ZCM																				
保守率	良	0.63	0.6	56	44	37	32	54	43	36	31	50	41	35	30	46	38	33	29	26	
	中	0.6	0.8	66	55	48	42	63	53	47	42	59	50	44	40	54	47	42	38	35	
	否	0.56	1.0	72	62	55	50	70	60	54	49	64	57	51	47	60	54	49	45	41	
			1.25	78	69	62	57	75	67	61	56	70	63	58	54	65	59	55	51	47	
下方投影面積	c m <sup>2</sup>		1.5	82	74	68	63	79	72	66	61	73	68	63	59	68	64	60	56	51	
	等価発光面積		c m <sup>2</sup>	2.0	87	81	75	71	84	78	73	69	79	74	70	66	73	69	66	63	57
取付高さ	器具間隔最大限		2.5	91	85	80	76	88	82	78	74	82	78	74	71	76	73	70	67	62	
	横方向 (A)	縦方向 (B)	3.0	93	88	84	80	90	85	82	78	84	80	77	74	78	75	73	71	65	
H m	1.27 H m	1.27 H m	4.0	96	92	88	85	93	89	86	83	87	84	81	79	81	79	77	75	68	
			5.0	97	94	91	89	94	91	89	86	88	86	84	82	83	81	79	78	71	
			7.0	99	97	95	93	96	94	92	90	90	89	87	86	85	83	82	81	74	
			10.0	101	99	98	96	98	96	95	93	92	91	89	88	86	85	84	83	76	

