

屋内照明器具特性	
品番 (品名)	LGC45820
光源	LED6500_70_4120 x1 4120.0 lm
管理番号	K0182157(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	11%	床	10%				10%				10%				10%				0%				
下方光束	89%	室指数	照明率 (X0.01)																				ZCM
保守率	良 0.63 中 0.6 否 0.56	0.6	55	43	35	29	53	42	34	29	49	40	33	28	46	38	32	28	25				
		0.8	64	53	45	39	62	52	44	39	58	49	43	38	55	47	41	37	34				
		1.0	71	60	52	46	68	58	51	46	64	56	49	44	60	53	47	43	40				
		1.25	77	67	59	53	74	65	58	53	69	62	56	51	65	59	54	50	46				
下方投影面積	c m ²	1.5	81	72	65	59	78	70	63	58	73	66	61	56	69	63	58	54	50				
		2.0	86	78	72	67	84	77	71	66	79	73	68	64	74	69	65	62	57				
取付高さ	器具間隔最大限		2.5	90	83	77	73	87	81	76	71	82	77	73	69	77	73	70	66	62			
	横方向 (A)	縦方向 (B)	3.0	92	86	81	77	89	84	80	75	85	80	76	73	80	76	73	70	65			
1.5m	1.97m	1.95m	4.0	95	91	86	83	93	88	85	81	88	84	81	78	83	80	77	75	70			
2	2.6	2.57	5.0	97	93	90	86	95	91	88	85	90	87	84	81	85	83	80	78	73			
2.5	3.25	3.21	7.0	99	96	94	91	97	94	92	89	92	90	88	86	88	86	84	82	77			
3	3.87	3.83	10.0	101	99	97	95	99	97	95	93	94	92	91	89	89	88	87	86	80			

