

屋内照明器具特性

品番 (品名)	LGC25834														
光源	LED6200_70_3450 x1 3450.0 lm														
管理番号	K0157935(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%									
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%									
		床	10%				10%				10%				10%				0%									
上方光束	5%	室指数																										
下方光束	95%	照明率 (X0.01)																										
		ZCM																										
保守率	良	0.63	0.6	0.5	0.4	0.3	0.2	0.1	0.6	0.5	0.4	0.3	0.2	0.1	0.6	0.5	0.4	0.3	0.2	0.1	0.6	0.5	0.4	0.3	0.2	0.1		
	中	0.6	0.8	0.7	0.6	0.5	0.4	0.3	0.8	0.7	0.6	0.5	0.4	0.3	0.8	0.7	0.6	0.5	0.4	0.3	0.8	0.7	0.6	0.5	0.4	0.3		
	否	0.56	1.0	0.9	0.8	0.7	0.6	0.5	1.0	0.9	0.8	0.7	0.6	0.5	1.0	0.9	0.8	0.7	0.6	0.5	1.0	0.9	0.8	0.7	0.6	0.5		
			1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0
下方投影面積	cm ²																											
等価発光面積	cm ²																											
取付高さ	器具間隔最大限																											
	横方向 (A)	縦方向 (B)																										
1.5m	1.96m	1.97m																										
2	2.6	2.61																										
2.5	3.17	3.19																										
3	3.81	3.82																										

