

# 屋内照明器具特性

|         |                    |          |  |
|---------|--------------------|----------|--|
| 品番 (品名) | XND3558WN          |          |  |
| 光源      | LED5000_80_4080 ×1 | 4080.0lm |  |
| 管理番号    | K0179566(0)DB1     |          |  |
| BZ分類    | BZ1                |          |  |

| 器具効率   | 100%    | 天井              | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |         |                 | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束   | 0%      | 反射率             | 壁           | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束   | 100%    |                 | 床           | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |         | 室指数             | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良       | 0.76            | 0.6         | 74  | 65  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 59  | 56  | 69  | 63  | 59  | 56  | 54 |
|        | 中       | 0.72            | 0.8         | 82  | 75  | 70  | 66  | 81  | 74  | 69  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 68  | 65  | 64 |
|        | 否       | 0.64            | 1.0         | 87  | 81  | 76  | 72  | 86  | 80  | 76  | 72  | 84  | 79  | 75  | 72  | 82  | 78  | 74  | 72  | 70 |
| 下方投影面積 | 等価発光面積  | cm <sup>2</sup> | 1.25        | 92  | 86  | 82  | 78  | 91  | 85  | 81  | 78  | 89  | 84  | 80  | 77  | 87  | 83  | 80  | 77  | 75 |
|        |         |                 | 1.5         | 95  | 90  | 86  | 82  | 93  | 89  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 86  | 83  | 81  | 79 |
| 取付高さ   | 器具間隔最大限 |                 | 2.0         | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84 |
|        | 横方向 (A) | 縦方向 (B)         | 2.5         | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |
| Hm     | 0.74Hm  | 0.74Hm          | 3.0         | 102 | 99  | 96  | 94  | 101 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
|        |         |                 | 4.0         | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 96  | 95  | 94  | 92 |
|        |         |                 | 5.0         | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |         |                 | 7.0         | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|        |         |                 | 10.0        | 107 | 106 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 96 |

