

屋内照明器具特性	
品番 (品名)	NNF 2 1 2 3 3 K
光源	LDL20S.N/11/12-K(960) ×1 960.0 1 m
管理番号	K0125043(0)DR1
BZ分類	BZ6

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	16 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	73 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	47	36	29	24	45	35	28	23	41	32	27	22	37	30	25	21	18	
		0.8	55	44	37	31	52	42	36	31	48	40	34	29	44	37	32	28	24	
		1.0	60	50	42	37	57	48	41	36	52	45	39	34	48	41	36	33	29	
		1.25	65	55	48	43	62	53	47	42	57	50	44	40	52	46	41	37	33	
下方投影面積	c m ²	1.5	68	60	53	47	65	57	51	46	60	53	48	44	55	49	45	41	36	
		2.0	73	66	59	54	70	63	58	53	65	59	54	50	59	55	51	47	42	
取付高さ	器具間隔最大限		2.5	76	70	64	59	73	67	62	58	68	63	58	54	62	58	54	46	
	横方向 (A)	縦方向 (B)	3.0	79	73	68	63	76	70	65	61	70	65	61	58	64	61	57	54	48
1.5m	1.53 m	1.9 m	4.0	82	77	72	68	79	74	70	66	73	69	66	63	67	64	61	59	53
2	2.03	2.49	5.0	84	79	76	72	81	77	73	70	75	71	69	66	69	67	64	62	55
2.5	2.54	3.09	7.0	86	83	80	77	83	80	77	74	77	75	72	70	72	69	68	66	59
3	3.05	3.69	10.0	88	85	83	81	85	82	80	78	79	77	75	74	73	72	70	69	62

