

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 8 5 J
光源	LED_FULL5000_85_5030 ×1 5030.0 1 m
管理番号	K0182015 (0) D 1
B Z 分類	BZ5

器具効率	100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	70 %	室指数	床	10 %				10 %				10 %				10 %				0 %
下方光束	30 %		照明率 (X0.01) ZCM																	
保守率	良 中 否 0.83 0.81 0.77	0.6	47	36	29	24	42	32	26	22	33	26	21	18	24	20	16	14	8	
		0.8	55	45	37	32	49	40	34	30	39	32	28	24	29	25	21	19	11	
		1.0	61	51	44	39	55	46	40	36	43	37	33	29	32	28	25	23	13	
		1.25	66	58	51	46	60	52	46	42	47	42	37	34	35	32	29	27	15	
下方投影面積	c m ²	1.5	70	62	56	51	63	56	51	46	50	45	41	38	38	34	32	29	17	
		2.0	75	69	63	58	68	62	57	53	54	50	46	43	41	38	36	34	19	
取付高さ	器具間隔最大限		2.5	79	73	68	64	71	66	62	58	56	53	50	47	43	40	38	21	
	横方向 (A)	縦方向 (B)	3.0	81	76	72	68	73	69	65	62	58	55	52	50	44	42	40	22	
1.5m	2.16 m	2.09 m	4.0	84	80	76	73	76	72	69	67	60	58	56	54	46	44	43	23	
2	2.87	2.69	5.0	86	82	79	76	77	75	72	70	62	60	58	56	47	46	44	24	
2.5	3.58	3.31	7.0	88	85	83	81	79	77	75	73	63	62	61	59	48	47	46	26	
3	4.3	3.93	10.0	89	87	86	84	81	79	78	76	65	64	63	62	49	49	48	27	

