

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 8 5 J
光源	LED_BASE5000_85_3550 ×1 3550.0 1 m
管理番号	K0182016(0)D 1
BZ分類	BZ6/1.8/BZ7/6.0/BZ8/8.5/BZ9

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		100%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		0%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.83	0.6	43	33	26	22	37	28	23	19	25	20	16	13	14	11	9	8	0	
	中	0.81	0.8	51	41	34	29	43	35	30	25	29	24	21	18	17	14	12	11	0	
	否	0.77	1.0	56	47	40	35	48	41	35	31	33	28	25	22	19	16	14	13	0	
	下方投影面積	c m ²		1.25	61	53	47	42	53	46	40	36	36	32	28	26	21	18	17	15	0
等価発光面積	c m ²		1.5	65	57	51	47	56	49	44	40	38	34	31	29	22	20	18	17	0	
	c m ²		2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0	
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	24	22	21	0	
	横方向 (A)	縦方向 (B)																			
1.5m	1.39 m	1.96 m	3.0	75	70	66	62	65	61	57	54	45	42	40	38	26	25	24	23	0	
2	1.82	2.5	4.0	78	74	71	68	67	64	61	59	46	45	43	41	27	26	25	24	0	
2.5	2.25	3.08	5.0	80	76	73	71	69	66	64	61	48	46	45	43	28	27	26	25	0	
3	2.71	3.68	7.0	82	79	77	75	70	68	67	65	49	48	47	46	29	28	27	27	0	
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	29	28	28	0	

