

屋内照明器具特性

品番 (品名)	LGC35821									
光源	LED6200_70_3400 x1					3400.0 lm				
管理番号	K0157432(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		87%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.6	0.56	0.6	55	43	35	30	53	42	35	30	49	40	33	29	46	38	32	28	25
	中	0.6	0.6	0.6	0.6	0.8	64	53	45	40	62	52	44	39	58	49	43	38	54	47	41	37	33
	否	0.56	0.56	0.56	0.56	1.0	71	60	52	47	68	58	51	46	64	55	49	44	59	52	47	43	39
	0.56	0.56	0.56	0.56	1.25	76	67	59	53	74	65	58	53	69	61	55	51	64	58	53	49	45	
下方投影面積	cm ²		1.5	80	71	64	59	78	69	63	58	73	66	60	56	68	62	58	54	49	49		
	等価発光面積		cm ²	2.0	86	78	72	67	83	76	70	65	78	72	67	63	73	68	64	60	56		
取付高さ	器具間隔最大限		2.5	89	83	77	72	86	80	75	71	81	76	72	68	76	72	68	65	60			
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	89	83	79	75	83	79	75	72	78	75	72	69	63			
1.5m	1.81m	1.84m	4.0	95	90	86	82	92	88	84	80	87	83	80	77	82	79	76	74	68			
2	2.39	2.43	5.0	97	93	89	86	94	90	87	84	89	86	83	80	84	81	79	77	71			
2.5	2.91	2.95	7.0	99	96	93	90	96	93	91	88	91	89	87	84	86	84	82	81	75			
3	3.49	3.54	10.0	101	98	96	94	98	96	94	92	93	91	90	88	88	87	85	84	78			

