

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 8 6 J
光源	LED_FULL4000_85_4620 ×1 4620.0 1 m
管理番号	K0182015 (0) D 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	70 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	30 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	47	36	29	24	42	32	26	22	33	26	21	18	24	20	16	14	8
	中	0.81	0.8	55	45	37	32	49	40	34	30	39	32	28	24	29	25	21	19	11
	否	0.77	1.0	61	51	44	39	55	46	40	36	43	37	33	29	32	28	25	23	13
			1.25	66	58	51	46	60	52	46	42	47	42	37	34	35	32	29	27	15
下方投影面積		cm ²	1.5	70	62	56	51	63	56	51	46	50	45	41	38	38	34	32	29	17
等価発光面積		cm ²	2.0	75	69	63	58	68	62	57	53	54	50	46	43	41	38	36	34	19
取付高さ	器具間隔最大限		2.5	79	73	68	64	71	66	62	58	56	53	50	47	43	40	38	37	21
	横方向 (A)	縦方向 (B)	3.0	81	76	72	68	73	69	65	62	58	55	52	50	44	42	40	39	22
1.5m	2.16 m	2.09 m	4.0	84	80	76	73	76	72	69	67	60	58	56	54	46	44	43	42	23
2	2.87	2.69	5.0	86	82	79	76	77	75	72	70	62	60	58	56	47	46	44	43	24
2.5	3.58	3.31	7.0	88	85	83	81	79	77	75	73	63	62	61	59	48	47	46	46	26
3	4.3	3.93	10.0	89	87	86	84	81	79	78	76	65	64	63	62	49	49	48	47	27

