

|          |                                    |
|----------|------------------------------------|
| 屋内照明器具特性 |                                    |
| 品番(品名)   | NNF41887J                          |
| 光源       | LED_FULLL3500_85_4620 ×1 4620.0 1m |
| 管理番号     | K0182015(0)D 1                     |
| BZ分類     | BZ5                                |

|        |         |                 |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 70%     | 床               | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 30%     | 室指数             | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.83            | 0.6           | 47 | 36 | 29 | 24  | 42 | 32 | 26 | 22  | 33 | 26 | 21 | 18  | 24 | 20 | 16 | 14  | 8  |
|        | 中       | 0.81            | 0.8           | 55 | 45 | 37 | 32  | 49 | 40 | 34 | 30  | 39 | 32 | 28 | 24  | 29 | 25 | 21 | 19  | 11 |
|        | 否       | 0.77            | 1.0           | 61 | 51 | 44 | 39  | 55 | 46 | 40 | 36  | 43 | 37 | 33 | 29  | 32 | 28 | 25 | 23  | 13 |
|        |         |                 | 1.25          | 66 | 58 | 51 | 46  | 60 | 52 | 46 | 42  | 47 | 42 | 37 | 34  | 35 | 32 | 29 | 27  | 15 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 70 | 62 | 56 | 51  | 63 | 56 | 51 | 46  | 50 | 45 | 41 | 38  | 38 | 34 | 32 | 29  | 17 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 75 | 69 | 63 | 58  | 68 | 62 | 57 | 53  | 54 | 50 | 46 | 43  | 41 | 38 | 36 | 34  | 19 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 79 | 73 | 68 | 64  | 71 | 66 | 62 | 58  | 56 | 53 | 50 | 47  | 43 | 40 | 38 | 37  | 21 |
|        | 横方向(A)  | 縦方向(B)          | 3.0           | 81 | 76 | 72 | 68  | 73 | 69 | 65 | 62  | 58 | 55 | 52 | 50  | 44 | 42 | 40 | 39  | 22 |
| 1.5m   | 2.16m   | 2.09m           | 4.0           | 84 | 80 | 76 | 73  | 76 | 72 | 69 | 67  | 60 | 58 | 56 | 54  | 46 | 44 | 43 | 42  | 23 |
| 2      | 2.87    | 2.69            | 5.0           | 86 | 82 | 79 | 76  | 77 | 75 | 72 | 70  | 62 | 60 | 58 | 56  | 47 | 46 | 44 | 43  | 24 |
| 2.5    | 3.58    | 3.31            | 7.0           | 88 | 85 | 83 | 81  | 79 | 77 | 75 | 73  | 63 | 62 | 61 | 59  | 48 | 47 | 46 | 46  | 26 |
| 3      | 4.3     | 3.93            | 10.0          | 89 | 87 | 86 | 84  | 81 | 79 | 78 | 76  | 65 | 64 | 63 | 62  | 49 | 49 | 48 | 47  | 27 |

