

# 屋内照明器具特性

品番 (品名)	LSEB1186K														
光源	LED6200_70_5300 x1 5300.0lm														
管理番号	K0183805(0)D1														
BZ分類	BZ5														

器具効率	100%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
			床	10%				10%				10%				10%				0%
上方光束	6%	室指数	照明率 ( X0.01 )																ZCM	
下方光束	94%																			
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.3	3.5	3.0	5.4	4.2	3.5	2.9	5.1	4.0	3.4	2.9	4.8	3.9	3.3	2.8	2.6	
		0.8	6.5	5.3	4.5	4.0	6.3	5.2	4.5	3.9	6.0	5.0	4.4	3.8	5.6	4.8	4.2	3.8	3.5	
		1.0	7.1	6.1	5.3	4.7	6.9	5.9	5.2	4.6	6.6	5.7	5.0	4.5	6.2	5.5	4.9	4.5	4.2	
		1.25	7.7	6.7	6.0	5.4	7.5	6.6	5.9	5.3	7.1	6.3	5.7	5.2	6.7	6.1	5.6	5.1	4.8	
下方投影面積 等価発光面積	c m <sup>2</sup>	1.5	8.1	7.2	6.5	6.0	7.9	7.1	6.4	5.9	7.5	6.8	6.2	5.8	7.1	6.5	6.0	5.6	5.3	
		2.0	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.5	7.7	7.2	6.7	6.4	6.0	
		2.5	9.1	8.4	7.8	7.3	8.8	8.2	7.7	7.2	8.4	7.9	7.4	7.1	8.0	7.6	7.2	6.9	6.5	
取付高さ H m	器具間隔最大限		3.0	9.3	8.7	8.2	7.8	9.1	8.5	8.1	7.7	8.7	8.2	7.8	7.5	8.3	7.9	7.6	7.3	6.9
	横方向 (A)	縦方向 (B)	4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.6	8.2	9.0	8.6	8.3	8.0	8.6	8.3	8.0	7.8	7.4
	1.27H m	1.27H m	5.0	9.8	9.4	9.1	8.7	9.6	9.2	8.9	8.6	9.2	8.9	8.6	8.3	8.8	8.6	8.3	8.1	7.7
			7.0	10.0	9.7	9.5	9.2	9.8	9.6	9.3	9.1	9.4	9.2	9.0	8.8	9.1	8.9	8.7	8.5	8.1
			10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.6	9.5	9.3	9.1	9.3	9.1	9.0	8.9	8.4

