

# 屋内照明器具特性

品番 (品名)	LGC45833									
光源	LED6200_70_4500 x1 4500.0 lm									
管理番号	K0157936(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	5%	室指数																		照明率 ( X0.01)																		ZCM																	
下方光束	95%																																																						
保守率	良 中 否	0.63	0.6	0.56	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25																																	
		0.6	0.6	0.6	0.6	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	34																																	
		0.56	0.56	0.56	0.56	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41																																	
		0.56	0.56	0.56	0.56	77	67	59	53	75	65	58	52	71	63	57	52	67	61	55	51	48																																	
下方投影面積	c m <sup>2</sup>	1.25	1.5	2.0	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53																																		
		2.0	2.5	3.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60																																		
取付高さ	器具間隔最大限		2.5		90	83	78	73	88	82	76	72	84	79	74	70	80	76	72	69	65																																		
	横方向 (A)	縦方向 (B)	3.0	3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69																																		
1.5m	1.96m	1.96m	4.0	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74																																		
2	2.6	2.6	5.0	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	77																																		
2.5	3.17	3.18	7.0	7.0	101	97	94	92	99	96	93	90	95	92	90	88	91	89	87	86	82																																		
3	3.81	3.81	10.0	10.0	102	100	98	96	100	98	96	94	97	95	93	92	93	92	91	89	85																																		

