

屋内照明器具特性

品番 (品名)	LGC35825														
光源	LED6200_70_3600 x1 3600.0 lm														
管理番号	K0157435(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 (X0.01)																ZCM		
下方光束	95%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	36	31	55	43	36	31	52	42	35	30	49	40	34	30	28		
		0.8	66	54	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37		
		1.0	72	62	54	48	71	61	53	48	67	58	52	47	64	56	51	46	44		
		1.25	78	69	61	55	76	67	60	55	73	65	59	54	69	63	57	53	50		
下方投影面積	c m ²	1.5	82	73	67	61	80	72	66	60	77	70	64	59	73	67	62	58	55		
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	74	69	66	62		
取付高さ	器具間隔最大限		2.5	91	85	79	75	89	83	78	74	86	80	76	72	82	78	74	71	67	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	84	81	77	75	71	
1.5m	1.88m	1.87m	4.0	97	92	88	85	95	91	87	84	91	88	85	82	88	85	82	80	76	
2	2.48	2.47	5.0	99	95	92	88	97	93	90	87	93	90	88	85	90	87	85	83	79	
2.5	3.02	3.01	7.0	101	98	96	93	99	97	94	92	96	93	91	89	92	90	89	87	83	
3	3.63	3.61	10.0	103	101	99	97	101	99	97	96	98	96	94	93	94	93	92	90	86	

