

屋内照明器具特性

品番 (品名)	LGC51157K														
光源	LED6200_70_5050 x1 5050.0 lm														
管理番号	K0183775(0)D 1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	反射率	床	10%				10%				10%				10%				0%	
下方光束	96%		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	56	43	36	30	54	43	35	30	51	41	35	30	49	40	34	29	27	
	中	0.6	0.8	66	54	46	40	64	53	46	40	61	51	45	39	58	49	44	39	36	
	否	0.56	1.0	72	61	53	48	70	60	53	47	67	58	52	47	63	56	50	46	43	
			1.25	78	68	61	55	76	67	60	55	72	65	58	54	69	62	57	53	50	
下方投影面積			1.5	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55	
等価発光面積			2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62	
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	70	67	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	86	82	78	88	83	79	76	84	81	77	74	71	
Hm	1.26Hm	1.26Hm	4.0	97	92	88	84	95	91	87	83	91	88	84	81	88	85	82	79	76	
			5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79	
			7.0	101	98	95	93	99	97	94	92	96	93	91	89	92	90	89	87	83	
			10.0	103	101	99	97	101	99	97	95	98	96	94	93	94	93	91	90	86	

