

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGC31162K |
| 光源 | LED6200_70_4299 x1 4299.0lm |
| 管理番号 | K0183808(0)D1 |
| BZ分類 | BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------------------------|---------|-------------|-----|-----|----|-----|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 8% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 92% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.63 中 0.6 否 0.56 | 0.6 | 55 | 42 | 35 | 29 | 53 | 42 | 34 | 29 | 50 | 40 | 33 | 28 | 47 | 38 | 32 | 28 | 25 | |
| | | 0.8 | 64 | 53 | 45 | 39 | 62 | 52 | 44 | 38 | 59 | 49 | 43 | 38 | 55 | 47 | 41 | 37 | 34 | |
| | | 1.0 | 71 | 60 | 52 | 46 | 69 | 59 | 51 | 46 | 65 | 56 | 50 | 44 | 61 | 54 | 48 | 43 | 40 | |
| | | 1.25 | 77 | 67 | 59 | 53 | 74 | 65 | 58 | 53 | 70 | 62 | 56 | 51 | 66 | 60 | 54 | 50 | 47 | |
| 下方投影面積 | cm ² | 1.5 | 81 | 72 | 64 | 59 | 78 | 70 | 63 | 58 | 74 | 67 | 61 | 56 | 70 | 64 | 59 | 55 | 51 | |
| | | 2.0 | 86 | 79 | 72 | 67 | 84 | 77 | 71 | 66 | 80 | 74 | 68 | 64 | 75 | 70 | 66 | 62 | 58 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 90 | 83 | 78 | 73 | 88 | 81 | 76 | 72 | 83 | 78 | 73 | 69 | 79 | 75 | 71 | 67 | 63 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 92 | 87 | 81 | 77 | 90 | 85 | 80 | 76 | 86 | 81 | 77 | 73 | 81 | 78 | 74 | 71 | 67 |
| Hm | 1.26Hm | 1.26Hm | 4.0 | 96 | 91 | 87 | 83 | 93 | 89 | 85 | 81 | 89 | 85 | 82 | 79 | 85 | 82 | 79 | 76 | 72 |
| | | | 5.0 | 98 | 94 | 90 | 87 | 95 | 92 | 88 | 85 | 91 | 88 | 85 | 82 | 87 | 84 | 82 | 80 | 75 |
| | | | 7.0 | 100 | 97 | 94 | 91 | 98 | 95 | 92 | 90 | 93 | 91 | 89 | 87 | 89 | 87 | 85 | 84 | 79 |
| | | | 10.0 | 102 | 100 | 97 | 95 | 100 | 97 | 96 | 94 | 95 | 94 | 92 | 90 | 91 | 90 | 88 | 87 | 82 |

