

屋内照明器具特性	
品番 (品名)	NYM20216
光源	LED5000_85_50400 ×1 50400.0 1m
管理番号	K0184476(0)DR1
BZ分類	BZ1/1.4/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	床	10%				10%				10%				10%				0%
下方光束	100%	室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.83 0.81 0.77	0.6	74	66	61	57	73	66	61	57	72	65	60	57	70	64	60	57	55
		0.8	82	74	69	65	81	73	69	65	79	72	68	65	77	71	68	64	63
		1.0	86	79	74	71	85	79	74	70	83	77	73	70	81	76	73	70	68
		1.25	90	84	79	76	89	83	79	75	87	82	78	75	85	81	77	74	73
下方投影面積	c m ²	1.5	93	87	83	79	92	87	82	79	89	85	81	78	87	84	80	78	76
		2.0	97	92	88	85	95	91	87	84	93	89	86	84	91	88	85	83	81
取付高さ	器具間隔最大限		2.5	99	95	91	89	98	94	91	88	95	92	89	87	93	90	88	86
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	89	94	92	90	88
H m	0.84 H m	0.84 H m	4.0	102	99	97	95	101	98	96	94	99	96	95	93	96	95	93	91
			5.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93
			7.0	105	103	101	100	104	102	100	99	101	100	99	97	99	98	97	96
			10.0	106	105	103	102	105	103	102	101	102	101	100	99	100	99	98	95

