

屋内照明器具特性

品番 (品名)	LGB51033									
光源	LED5000_70_1110 x1 1110.0 lm									
管理番号	K0154734(0)DB1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		16%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		84%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.69	0.6	53	40	33	27	51	39	32	27	47	37	30	26	43	35	29	25	22	
	中	0.67	0.8	62	50	42	36	60	49	41	36	55	46	39	34	51	43	37	33	30	
	否	0.63	1.0	69	57	49	43	66	56	48	43	61	52	46	41	56	49	44	39	35	
			0.63	1.25	74	64	57	51	72	62	55	50	66	58	52	48	61	55	50	46	41
下方投影面積			cm ²	1.5	79	69	62	56	76	67	60	55	70	63	57	53	65	59	54	50	45
			cm ²	2.0	84	76	70	64	81	74	68	63	75	69	64	60	70	65	61	57	52
取付高さ	器具間隔最大限			2.5	88	81	75	70	85	78	73	68	79	74	69	65	74	69	66	62	57
	横方向 (A)	縦方向 (B)		3.0	90	84	79	74	87	82	77	73	81	77	73	69	76	72	69	66	60
1.5m	2.05m	1.89m		4.0	94	89	84	80	91	86	82	78	85	81	78	75	79	76	73	71	65
2	2.72	2.49		5.0	96	91	88	84	93	89	85	82	87	84	81	78	81	79	76	74	68
2.5	3.41	3.09		7.0	98	95	92	89	95	92	89	87	89	87	85	82	84	82	80	78	72
3	4.07	3.7		10.0	100	98	95	93	97	95	93	91	91	89	88	86	86	84	83	82	75

