

屋内照明器具特性

品番 (品名)	LGB15187														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0185512(0)DR1														
BZ分類	BZ4/0.7/BZ3														

器具効率	88%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	0% 88%	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.67 0.63 0.56	0.6	53	43	37	32	52	43	37	32	50	42	36	32	48	41	36	32	30	
		0.8	63	54	48	43	62	53	48	43	60	52	47	43	58	51	46	43	41	
		1.0	69	61	55	51	68	61	55	51	66	59	54	51	64	58	54	50	49	
		1.25	75	68	62	58	74	67	62	58	71	65	61	58	69	64	60	57	55	
下方投影面積 等価発光面積	c m ² c m ²	1.5	78	72	67	63	77	71	66	63	75	70	65	62	72	68	65	62	60	
		2.0	83	77	73	70	81	77	73	69	79	75	72	69	77	73	71	68	66	
取付 高さ	器具間隔最大限		2.5	85	81	77	74	84	80	77	74	82	78	75	73	80	77	74	72	70
	横方向 (A) H m	縦方向 (B) H m	3.0	87	83	80	77	86	82	79	77	84	81	78	76	81	79	77	75	73
			4.0	89	86	84	81	88	85	83	81	86	84	82	80	84	82	80	79	76
			5.0	91	88	86	84	89	87	85	83	87	85	84	82	85	84	82	81	79
			7.0	92	90	89	87	91	89	88	86	89	87	86	85	87	86	85	84	81
			10.0	93	92	91	90	92	91	90	89	90	89	88	87	88	87	86	86	83

