

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | XNS 0 6 3 0 WB K    |           |
| 光源      | LED4000_85_495 x1   | 495.0 l m |
| 管理番号    | K0183321 ( 0 ) DB 1 |           |
| B Z 分類  | B Z 1               |           |

|        |                  |          |               |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     |     |     |  |  |       |
|--------|------------------|----------|---------------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|--|--|-------|
| 器具効率   | 100 %            | 天井       | 80 %          |      |     |     | 70 % |      |     |     | 50 % |      |     |     | 30 % |      |     |     | 0 % |     |  |  |       |
|        | 上方光束<br>0 %      |          | 反射率           | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10  | 0 % |  |  |       |
| 下方光束   | 100 %            | 床        |               | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |     | 0 % |  |  |       |
| 室指数    |                  |          | 照明率 ( X0.01 ) |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     |     |     |  |  | Z C M |
| 保守率    | 良 0.81           | 0.6      | 73            | 65   | 60  | 56  | 73   | 65   | 59  | 56  | 71   | 64   | 59  | 56  | 69   | 63   | 59  | 56  | 54  |     |  |  |       |
|        | 中 0.77           | 0.8      | 82            | 75   | 70  | 66  | 81   | 75   | 70  | 66  | 80   | 74   | 69  | 66  | 78   | 73   | 69  | 66  | 64  |     |  |  |       |
|        | 否 0.68           | 1.0      | 88            | 81   | 77  | 73  | 87   | 81   | 76  | 73  | 85   | 80   | 76  | 73  | 83   | 78   | 75  | 72  | 71  |     |  |  |       |
|        |                  | 1.25     | 92            | 87   | 82  | 79  | 91   | 86   | 82  | 79  | 89   | 85   | 81  | 78  | 87   | 83   | 80  | 78  | 76  |     |  |  |       |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 95            | 90   | 86  | 83  | 94   | 89   | 85  | 83  | 92   | 88   | 85  | 82  | 90   | 86   | 84  | 81  | 80  |     |  |  |       |
| 等価発光面積 | c m <sup>2</sup> | 2.0      | 98            | 94   | 91  | 88  | 97   | 93   | 90  | 88  | 95   | 92   | 89  | 87  | 93   | 90   | 88  | 86  | 84  |     |  |  |       |
| 取付高さ   | 器具間隔最大限          |          | 2.5           | 100  | 97  | 94  | 92   | 99   | 96  | 93  | 91   | 97   | 94  | 92  | 90   | 95   | 93  | 91  | 89  | 87  |  |  |       |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0           | 102  | 99  | 96  | 94   | 101  | 98  | 96  | 94   | 98   | 96  | 94  | 92   | 96   | 94  | 93  | 91  | 89  |  |  |       |
| H m    | 1.24 H m         | 1.24 H m | 4.0           | 103  | 101 | 99  | 97   | 102  | 100 | 98  | 97   | 100  | 98  | 97  | 95   | 98   | 96  | 95  | 94  | 92  |  |  |       |
|        |                  |          | 5.0           | 104  | 103 | 101 | 99   | 103  | 102 | 100 | 99   | 101  | 100 | 98  | 97   | 99   | 98  | 97  | 96  | 93  |  |  |       |
|        |                  |          | 7.0           | 106  | 104 | 103 | 102  | 104  | 103 | 102 | 101  | 102  | 101 | 100 | 99   | 100  | 99  | 98  | 98  | 95  |  |  |       |
|        |                  |          | 10.0          | 106  | 105 | 104 | 104  | 105  | 104 | 103 | 103  | 103  | 102 | 102 | 101  | 101  | 100 | 100 | 99  | 96  |  |  |       |

