

# 屋内照明器具特性

|         |                                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB15188                                     |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD20001CQ1 ×1                      531.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0185500(0)DR1                               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ3                                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |         |                                       |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
|--------|---------|---------|---------------------------------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|
| 器具効率   | 87%     | 天井      | 80%                                   |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |
|        |         | 壁       | 70                                    | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |
| 上方光束   | 0%      | 床       | 10%                                   |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |
| 下方光束   | 87%     | 室指数     | 照明率 ( X0.01)                      ZCM |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 保守率    | 良       | 0.67    | 0.6                                   | 53 | 43 | 37 | 32  | 52 | 42 | 37 | 32  | 50 | 42 | 36 | 32  | 48 | 41 | 36 | 32 | 30 |
|        | 中       | 0.63    | 0.8                                   | 62 | 54 | 48 | 43  | 61 | 53 | 47 | 43  | 59 | 52 | 47 | 43  | 57 | 51 | 46 | 43 | 41 |
|        | 否       | 0.56    | 1.0                                   | 69 | 61 | 55 | 51  | 67 | 60 | 55 | 51  | 65 | 59 | 54 | 50  | 63 | 58 | 53 | 50 | 48 |
|        |         |         | 1.25                                  | 74 | 67 | 62 | 58  | 72 | 66 | 61 | 58  | 70 | 65 | 61 | 57  | 68 | 63 | 60 | 57 | 55 |
| 下方投影面積 |         |         | 1.5                                   | 77 | 71 | 66 | 62  | 76 | 70 | 66 | 62  | 73 | 69 | 65 | 62  | 71 | 67 | 64 | 61 | 59 |
|        |         |         | 2.0                                   | 81 | 76 | 72 | 69  | 80 | 75 | 72 | 69  | 78 | 74 | 71 | 68  | 76 | 72 | 70 | 67 | 65 |
| 取付高さ   | 器具間隔最大限 |         | 2.5                                   | 84 | 80 | 76 | 73  | 83 | 79 | 76 | 73  | 80 | 77 | 74 | 72  | 78 | 76 | 73 | 71 | 69 |
|        | 横方向 (A) | 縦方向 (B) | 3.0                                   | 85 | 82 | 79 | 76  | 84 | 81 | 78 | 76  | 82 | 79 | 77 | 75  | 80 | 78 | 76 | 74 | 72 |
| Hm     | 1.28Hm  | 1.28Hm  | 4.0                                   | 88 | 85 | 82 | 80  | 86 | 84 | 82 | 80  | 84 | 82 | 80 | 78  | 82 | 80 | 79 | 77 | 75 |
|        |         |         | 5.0                                   | 89 | 87 | 85 | 83  | 88 | 86 | 84 | 82  | 86 | 84 | 82 | 81  | 84 | 82 | 81 | 79 | 77 |
|        |         |         | 7.0                                   | 90 | 89 | 87 | 86  | 89 | 88 | 86 | 85  | 87 | 86 | 85 | 83  | 85 | 84 | 83 | 82 | 80 |
|        |         |         | 10.0                                  | 91 | 90 | 89 | 88  | 90 | 89 | 88 | 87  | 88 | 87 | 86 | 86  | 86 | 85 | 85 | 84 | 82 |

