

屋内照明器具特性

品番 (品名)	LGC21135K														
光源	LED6200_70_3699 x1 3699.0 lm														
管理番号	K0183773(0)D1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	6%	反射率	床	10%				10%				10%				10%				0%
下方光束	94%		室指数	照明率 (X0.01) ZCM																
保守率	良	0.63	0.6	55	43	35	30	54	42	35	29	51	40	34	29	48	39	33	28	26
	中	0.6	0.8	65	53	45	39	63	52	45	39	59	50	43	38	56	48	42	38	35
	否	0.56	1.0	71	60	52	46	69	59	52	46	65	57	50	45	62	55	49	44	41
			1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	61	55	51	48
下方投影面積			1.5	81	72	65	59	79	71	64	58	75	68	62	57	71	65	60	56	53
	等価発光面積		2.0	87	79	73	67	85	77	71	66	80	74	69	65	77	71	67	63	60
取付高さ	器具間隔最大限		2.5	90	84	78	73	88	82	77	72	84	79	74	70	80	76	72	68	65
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	85	80	76	86	82	78	74	83	79	75	72	68
Hm	1.25Hm	1.25Hm	4.0	96	91	87	83	94	89	85	82	90	86	83	80	86	83	80	77	73
			5.0	98	94	90	87	96	92	89	86	92	89	86	83	88	85	83	81	77
			7.0	100	97	94	92	98	95	93	90	94	92	90	88	91	89	87	85	81
			10.0	102	100	98	96	100	98	96	94	96	95	93	91	93	91	90	88	84

