

屋内照明器具特性	
品番 (品名)	LGC31162K
光源	LED6200_70_4299 x1 4299.0 lm
管理番号	K0183808(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.63 中 0.6 否 0.56	0.6	55	42	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25	
		0.8	64	53	45	39	62	52	44	38	59	49	43	38	55	47	41	37	34	
		1.0	71	60	52	46	69	59	51	46	65	56	50	44	61	54	48	43	40	
		1.25	77	67	59	53	74	65	58	53	70	62	56	51	66	60	54	50	47	
下方投影面積	cm <sup>2</sup>	1.5	81	72	64	59	78	70	63	58	74	67	61	56	70	64	59	55	51	
		2.0	86	79	72	67	84	77	71	66	80	74	68	64	75	70	66	62	58	
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	81	76	72	83	78	73	69	79	75	71	67	63
	横方向 (A)	縦方向 (B)	3.0	92	87	81	77	90	85	80	76	86	81	77	73	81	78	74	71	67
Hm	1.26Hm	1.26Hm	4.0	96	91	87	83	93	89	85	81	89	85	82	79	85	82	79	76	72
			5.0	98	94	90	87	95	92	88	85	91	88	85	82	87	84	82	80	75
			7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	85	84	79
			10.0	102	100	97	95	100	97	96	94	95	94	92	90	91	90	88	87	82

