

# 屋内照明器具特性

品番 (品名)	LGC31149K														
光源	LED6200_70_4000 x1 4000.0lm														
管理番号	K0168768(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%	
上方光束	6%	室指数	照明率 ( X0.01)																ZCM			
下方光束	94%																					
保守率	良 中 否	0.63	0.6	0.56	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26
		0.6	0.8	65	53	45	40	63	52	45	39	60	50	44	39	57	49	43	38	35		
		0.56	1.0	72	61	53	47	70	59	52	47	66	57	51	46	62	55	49	45	42		
			1.25	77	68	60	54	75	66	59	54	71	64	58	53	68	61	56	52	48		
下方投影面積	c m <sup>2</sup>	1.5	82	72	65	60	79	71	64	59	75	68	63	58	72	66	61	57	53			
		2.0	87	79	73	68	85	78	72	67	81	75	70	66	77	72	68	64	60			
取付高さ	器具間隔最大限		2.5	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65		
	横方向 (A)	縦方向 (B)	3.0	93	87	82	78	91	86	81	77	87	82	78	75	83	79	76	73	69		
H m	1.26 H m	1.26 H m	4.0	96	92	87	84	94	90	86	82	90	86	83	80	86	83	81	78	74		
			5.0	98	94	91	87	96	93	89	86	92	89	86	84	88	86	84	81	77		
			7.0	101	98	95	92	98	96	93	91	95	92	90	88	91	89	87	85	81		
			10.0	102	100	98	96	100	98	96	95	96	95	93	92	93	91	90	89	84		

