

屋内照明器具特性

品番 (品名)	LGC31151K														
光源	LED6200_70_3750 x1 3750.0 lm														
管理番号	K0168770(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	6%	反射率	床	10%				10%				10%				10%				0%
下方光束	94%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.63 0.6 0.56	0.6	57	45	37	32	55	44	37	32	52	42	36	31	50	41	35	31	28	
		0.8	67	55	48	42	65	54	47	42	61	52	46	41	58	51	45	40	38	
		1.0	73	63	55	49	71	61	54	49	68	59	53	48	64	57	52	47	45	
		1.25	79	69	62	57	77	68	61	56	73	66	60	55	70	63	58	54	51	
下方投影面積	c m ²	1.5	83	74	68	62	81	73	67	62	77	70	65	60	73	68	63	59	56	
		2.0	88	81	75	70	86	80	74	70	82	77	72	68	79	74	70	67	63	
取付高さ	器具間隔最大限		2.5	92	86	80	76	90	84	79	75	86	81	77	73	82	78	75	72	68
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	83	79	88	84	80	77	85	81	78	75	72
H m	1.21H m	1.21H m	4.0	97	93	89	86	95	91	88	85	91	88	85	82	88	85	83	80	76
			5.0	99	96	92	89	97	94	91	88	93	91	88	86	90	88	85	83	79
			7.0	101	99	96	94	99	97	95	92	96	94	92	90	92	90	89	87	83
			10.0	103	101	99	97	101	99	98	96	97	96	94	93	94	93	92	90	86

