

# 屋内照明器具特性

品番 (品名)	LGD9107	
光源	LLD5020LCC1 ×1	1085.0 lm
管理番号	K0187674 (2) DR1	
BZ分類	BZ1	

器具効率	97%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	77	70	65	62	76	69	65	62	74	69	65	62	73	68	65	62	61
	中	0.63	0.8	83	77	73	70	82	77	72	70	81	76	72	69	79	75	72	69	68
	否	0.56	1.0	87	82	78	75	86	81	77	74	85	80	77	74	83	79	76	74	72
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	91	86	82	79	90	85	82	79	88	84	81	78	86	83	80	78	77
			1.5	93	89	85	83	92	88	85	82	90	87	84	82	88	85	83	81	79
取付高さ	器具間隔最大限		2.5	98	95	92	90	97	94	92	90	95	92	90	89	93	91	89	88	86
	横方向 (A)	縦方向 (B)	3.0	99	96	94	92	98	96	93	92	96	94	92	90	94	92	91	89	87
Hm	0.45Hm	0.45Hm	4.0	100	98	97	95	99	97	96	94	97	96	94	93	95	94	93	92	90
			5.0	101	100	98	97	100	99	97	96	98	97	96	95	96	95	94	93	91
			7.0	102	101	100	99	101	100	99	98	99	98	97	96	97	96	96	95	92
			10.0	103	102	101	101	102	101	100	100	100	99	99	98	98	97	97	96	94

