

屋内照明器具特性

品番 (品名)	XNW2 0 6 2 WN		
光源	LED5000_85_1920 ×1	1920.0 1m	
管理番号	K0183311 (0) DB 1		
BZ分類	BZ1		

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	100 %		照明率 (X0.01)																				
保守率	良 中 否	0.81 0.77 0.68	室指数																				ZCM
			0.6	85	79	75	72	84	78	75	72	83	78	74	72	81	77	74	72	71			
下方投影面積	等価発光面積	cm ² cm ²	1.25	97	93	90	88	96	92	90	87	95	91	89	87	93	90	88	86	85			
			1.5	99	95	93	90	98	95	92	90	96	93	91	89	95	92	90	89	87	87		
取付高さ	器具間隔最大限		2.5	103	100	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92			
	横方向 (A)	縦方向 (B)	3.0	104	102	100	98	103	101	99	98	101	99	98	96	99	98	96	95	93			
Hm	0.79Hm	0.79Hm	4.0	105	103	102	100	104	102	101	100	102	101	99	98	100	99	98	97	95			
			5.0	106	104	103	102	105	103	102	101	102	101	101	100	101	100	99	98	96	96		
			7.0	107	105	105	104	105	104	104	103	103	102	102	101	101	100	99	97	97			
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98			

