

屋内照明器具特性

品番 (品名)	L G W 4 5 8 0 1																
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m																
管理番号	K0175935 (0) DR 1																
B Z 分類	BZ10																

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	52 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	39 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	3.8	2.7	1.9	1.4	3.4	2.4	1.7	1.3	2.7	1.9	1.4	1.0	2.0	1.4	1.0	0.7	0.2
	中	0.6	0.8	4.5	3.4	2.6	2.0	4.1	3.1	2.3	1.8	3.2	2.4	1.8	1.4	2.4	1.8	1.4	1.0	0.4
	否	0.56	1.0	5.1	3.9	3.1	2.5	4.5	3.6	2.8	2.3	3.6	2.8	2.3	1.8	2.7	2.1	1.7	1.3	0.5
			1.25	5.6	4.5	3.7	3.1	5.0	4.1	3.4	2.8	3.9	3.2	2.7	2.2	3.0	2.4	2.0	1.7	0.7
下方投影面積		cm ²	1.5	5.9	4.9	4.2	3.5	5.3	4.5	3.8	3.2	4.2	3.6	3.0	2.6	3.2	2.7	2.3	2.0	0.9
等価発光面積		cm ²	2.0	6.4	5.6	4.9	4.3	5.8	5.1	4.4	3.9	4.7	4.1	3.6	3.1	3.6	3.1	2.7	2.4	1.2
取付高さ	器具間隔最大限		2.5	6.8	6.0	5.4	4.8	6.2	5.5	4.9	4.4	4.9	4.4	4.0	3.6	3.8	3.4	3.1	2.8	1.5
	横方向 (A)	縦方向 (B)	3.0	7.0	6.3	5.7	5.2	6.4	5.8	5.2	4.8	5.2	4.7	4.3	3.9	4.0	3.6	3.3	3.0	1.7
Hm	0.00Hm	0.00Hm	4.0	7.4	6.8	6.3	5.8	6.7	6.2	5.7	5.3	5.5	5.0	4.7	4.3	4.3	4.0	3.7	3.4	2.0
			5.0	7.6	7.1	6.6	6.2	6.9	6.5	6.1	5.7	5.7	5.3	5.0	4.7	4.5	4.2	3.9	3.7	2.2
			7.0	7.9	7.4	7.1	6.7	7.2	6.8	6.5	6.2	5.9	5.6	5.4	5.1	4.7	4.5	4.3	4.1	2.5
			10.0	8.1	7.8	7.5	7.2	7.4	7.1	6.9	6.6	6.1	5.9	5.7	5.5	4.9	4.7	4.6	4.4	2.8

