

屋内照明器具特性

品番 (品名)	LGB51024															
光源	LED3500_70_1025 x1 1025.0lm															
管理番号	K0154734(0)DB1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	16%	室指数	照明率 (X0.01)																ZCM		
下方光束	84%																				
保守率	良 中 否	0.69	0.6	53	40	33	27	51	39	32	27	47	37	30	26	43	35	29	25	22	
		0.67	0.8	62	50	42	36	60	49	41	36	55	46	39	34	51	43	37	33	30	
			1.0	69	57	49	43	66	56	48	43	61	52	46	41	56	49	44	39	35	
		0.63	1.25	74	64	57	51	72	62	55	50	66	58	52	48	61	55	50	46	41	
下方投影面積	c m ²	1.5	79	69	62	56	76	67	60	55	70	63	57	53	65	59	54	50	45		
		2.0	84	76	70	64	81	74	68	63	75	69	64	60	70	65	61	57	52		
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	78	73	68	79	74	69	65	74	69	66	62	57	
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	87	82	77	73	81	77	73	69	76	72	69	66	60	
1.5m	2.05m	1.89m	4.0	94	89	84	80	91	86	82	78	85	81	78	75	79	76	73	71	65	
2	2.72	2.49	5.0	96	91	88	84	93	89	85	82	87	84	81	78	81	79	76	74	68	
2.5	3.41	3.09	7.0	98	95	92	89	95	92	89	87	89	87	85	82	84	82	80	78	72	
3	4.07	3.7	10.0	100	98	95	93	97	95	93	91	91	89	88	86	86	84	83	82	75	

