

屋内照明器具特性

品番 (品名)	SNCX31121									
光源	LED6200_70_4299 x1 4299.0 lm									
管理番号	K0182585(0)DR1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26
	中	0.6	0.8	65	54	46	40	63	53	45	40	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	47	70	60	53	47	66	58	51	46	63	55	50	45	42
			1.25	78	68	61	55	76	67	60	54	72	64	58	53	68	62	57	52	49
下方投影面積	cm ²		1.5	82	73	66	61	80	72	65	60	76	69	63	59	72	66	62	58	54
等価発光面積	cm ²		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	85	79	75	89	83	78	74	85	80	76	72	81	77	74	70	67
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	83	80	76	84	80	77	74	70
Hm	1.30Hm	1.30Hm	4.0	97	92	89	85	95	91	87	84	91	87	84	82	87	84	82	79	75
			5.0	99	95	92	89	97	93	90	87	93	90	87	85	89	87	85	83	79
			7.0	101	98	96	93	99	97	94	92	95	93	91	89	92	90	88	87	82
			10.0	103	101	99	97	101	99	97	96	97	96	94	93	94	92	91	90	85

