

屋内照明器具特性

品番 (品名) **LGB15493**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0185524(0)DR1**

BZ分類 **BZ1**

器具効率	87%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	87%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	73	67	64	61	72	67	64	61	71	66	63	61	70	66	63	61	60	
	中 0.63	0.8	78	73	70	68	77	73	70	67	76	72	69	67	75	71	69	67	66	
	否 0.56	1.0	81	77	74	72	80	77	74	71	79	76	73	71	78	75	73	71	70	
下方投影面積	等価発光面積	cm ²	1.25	84	80	77	75	83	80	77	75	82	79	76	75	80	78	76	74	73
			1.5	86	82	80	78	85	82	79	77	83	81	79	77	82	80	78	76	75
取付高さ	器具間隔最大限		2.0	88	85	83	81	87	84	82	81	85	83	82	80	84	82	81	79	78
	横方向 (A)	縦方向 (B)	2.5	89	87	85	83	88	86	84	83	86	85	83	82	85	83	82	81	79
Hm	0.47Hm	0.47Hm	3.0	90	88	86	85	89	87	86	84	87	86	85	83	86	84	83	82	81
			4.0	91	90	88	87	90	89	87	86	88	87	86	85	87	86	85	84	82
			5.0	92	90	89	88	91	90	89	88	89	88	87	86	87	86	86	85	83
			7.0	92	91	91	90	91	91	90	89	90	89	88	88	88	87	87	86	84
			10.0	93	92	92	91	92	91	91	90	90	90	89	89	88	88	87	87	85

