

屋内照明器具特性

品番 (品名) **LGB16188**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0185498(1)DR1**

BZ分類 **BZ1**

器具効率	91%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	91%	床		10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	75	70	66	63	75	69	66	63	73	69	65	63	72	68	65	63	62	
	中 0.63	0.8	81	76	73	70	80	76	72	70	79	75	72	70	78	74	71	69	68	
	否 0.56	1.0	85	80	77	74	84	80	77	74	82	79	76	74	81	78	75	74	72	
下方投影面積	等価発光面積	cm ²	1.25	88	84	81	78	87	83	80	78	85	82	80	78	84	81	79	77	76
			1.5	90	86	83	81	89	85	83	81	87	84	82	80	85	83	81	80	78
取付高さ	器具間隔最大限		2.5	93	91	89	87	92	90	88	87	91	89	87	86	89	87	86	85	83
	横方向 (A)	縦方向 (B)	3.0	94	92	90	89	93	91	90	88	91	90	88	87	90	88	87	86	84
Hm	0.47Hm	0.47Hm	4.0	95	94	92	91	94	93	92	90	93	91	90	89	91	90	89	88	86
			5.0	96	95	94	93	95	94	93	92	93	92	91	90	91	91	90	89	87
			7.0	97	96	95	94	96	95	94	93	94	93	93	92	92	91	91	90	88
			10.0	98	97	96	96	96	96	95	95	94	94	93	93	93	92	92	91	89

