

屋内照明器具特性	
品番 (品名)	LGB16188
光源	LLD20001CQ1 ×1                      531.0 lm
管理番号	K0185500(0)DR1
BZ分類	BZ4/0.7/BZ3

器具効率	87%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 ( X0.01)																		ZCM																	
下方光束	87%																																																						
保守率	良 0.67 中 0.63 否 0.56	0.6	53	43	37	32	52	42	37	32	50	42	36	32	48	41	36	32	30																																				
		0.8	62	54	48	43	61	53	47	43	59	52	47	43	57	51	46	43	41																																				
		1.0	69	61	55	51	67	60	55	51	65	59	54	50	63	58	53	50	48																																				
		1.25	74	67	62	58	72	66	61	58	70	65	61	57	68	63	60	57	55																																				
下方投影面積	cm <sup>2</sup>	1.5	77	71	66	62	76	70	66	62	73	69	65	62	71	67	64	61	59																																				
		2.0	81	76	72	69	80	75	72	69	78	74	71	68	76	72	70	67	65																																				
等価発光面積	cm <sup>2</sup>	2.5	84	80	76	73	83	79	76	73	80	77	74	72	78	76	73	71	69																																				
		3.0	85	82	79	76	84	81	78	76	82	79	77	75	80	78	76	74	72																																				
取付高さ	器具間隔最大限		4.0	88	85	82	80	86	84	82	80	84	82	80	78	82	80	79	77	75																																			
	横方向 (A)	縦方向 (B)	5.0	89	87	85	83	88	86	84	82	86	84	82	81	84	82	81	79	77																																			
Hm	1.28Hm	1.28Hm	7.0	90	89	87	86	89	88	86	85	87	86	85	83	85	84	83	82	80																																			
			10.0	91	90	89	88	90	89	88	87	88	87	86	86	86	85	85	84	82																																			

