

屋内照明器具特性

品番 (品名)	LGB16188	
光源	LLD2020CU1 ×1	468.0 lm
管理番号	K0185513(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	0.6	82	76	72	69	81	76	72	69	80	75	72	69	79	74	71	69	68
	中 0.63		0.8	88	83	79	76	87	82	79	76	86	81	78	76	84	80	78	76	74
	否 0.56		1.0	92	87	83	81	91	86	83	81	89	85	82	80	88	84	82	80	79
下方投影面積 等価発光面積	cm ²	cm ²	1.25	95	90	87	85	94	90	87	85	92	89	86	84	90	88	85	84	82
			1.5	97	93	90	88	96	92	90	87	94	91	89	87	92	90	88	86	85
取付高さ	器具間隔最大限		2.5	101	98	96	94	100	97	95	94	98	96	94	93	96	94	93	92	90
	横方向 (A)	縦方向 (B)	3.0	102	99	97	96	101	99	97	95	99	97	95	94	97	95	94	93	91
Hm	0.36Hm	0.36Hm	4.0	103	101	100	98	102	100	99	97	100	98	97	96	98	97	96	95	93
			5.0	104	102	101	100	102	101	100	99	100	99	98	97	98	98	97	96	94
			7.0	104	103	102	101	103	102	101	101	100	100	99	99	98	98	97	95	
			10.0	105	104	104	103	104	103	103	102	102	101	101	100	100	99	99	98	96

