

屋内照明器具特性	
品番 (品名)	LGB16189
光源	LLD2000LCE1 ×1                      531.0 lm
管理番号	K0185493(0)DR1
BZ分類	BZ4/0.7/BZ3

器具効率	90%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	90%	室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.67	0.6	5.5	4.5	3.8	3.4	5.4	4.4	3.8	3.4	5.2	4.3	3.8	3.3	5.0	4.2	3.7	3.3	3.2
	中	0.63	0.8	6.5	5.6	4.9	4.5	6.4	5.5	4.9	4.5	6.1	5.4	4.9	4.4	5.9	5.3	4.8	4.4	4.3
	否	0.56	1.0	7.1	6.3	5.7	5.3	7.0	6.2	5.7	5.3	6.8	6.1	5.6	5.2	6.6	6.0	5.6	5.2	5.0
			1.25	7.7	7.0	6.4	6.0	7.5	6.9	6.4	6.0	7.3	6.7	6.3	5.9	7.1	6.6	6.2	5.9	5.7
下方投影面積		cm <sup>2</sup>	1.5	8.0	7.4	6.9	6.5	7.9	7.3	6.8	6.5	7.7	7.1	6.7	6.4	7.4	7.0	6.6	6.3	6.2
等価発光面積		cm <sup>2</sup>	2.0	8.5	7.9	7.5	7.2	8.3	7.9	7.5	7.1	8.1	7.7	7.4	7.1	7.9	7.5	7.2	7.0	6.8
取付高さ	器具間隔最大限		2.5	8.7	8.3	7.9	7.6	8.6	8.2	7.9	7.6	8.4	8.0	7.7	7.5	8.2	7.9	7.6	7.4	7.2
	横方向 (A)	縦方向 (B)	3.0	8.9	8.5	8.2	7.9	8.8	8.4	8.1	7.9	8.6	8.3	8.0	7.8	8.3	8.1	7.9	7.7	7.5
Hm	1.27Hm	1.27Hm	4.0	9.1	8.8	8.6	8.4	9.0	8.7	8.5	8.3	8.8	8.6	8.4	8.2	8.6	8.4	8.2	8.1	7.8
			5.0	9.3	9.0	8.8	8.6	9.1	8.9	8.7	8.5	8.9	8.7	8.6	8.4	8.7	8.6	8.4	8.3	8.1
			7.0	9.4	9.2	9.1	8.9	9.3	9.1	9.0	8.8	9.1	8.9	8.8	8.7	8.9	8.8	8.7	8.6	8.3
			10.0	9.5	9.4	9.3	9.2	9.4	9.3	9.2	9.1	9.2	9.1	9.0	8.9	9.0	8.9	8.8	8.8	8.5

