

# 屋内照明器具特性

品番 (品名) **LGB16189**

光源 **LLD3020MLCB1 ×1** **715.0 lm**

管理番号 **K0185496(0)DR1**

BZ分類 **BZ1**

器具効率	80%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	80%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	0.6	65	60	57	55	65	60	57	55	64	59	57	54	63	59	56	54	53	
	中 0.63	0.8	70	66	63	61	70	66	63	60	69	65	62	60	67	64	62	60	59	
	否 0.56	1.0	74	70	67	64	73	69	66	64	72	68	66	64	70	68	65	64	63	
下方投影面積	cm <sup>2</sup>	1.25	76	73	70	68	75	72	70	68	74	71	69	67	73	70	68	67	66	
		1.5	78	75	72	70	77	74	72	70	76	73	71	70	74	72	71	69	68	
等価発光面積	cm <sup>2</sup>	2.0	80	78	75	74	79	77	75	73	78	76	74	73	76	75	73	72	71	
		2.5	81	79	77	76	81	79	77	75	79	77	76	75	77	76	75	74	72	
取付高さ	器具間隔最大限		3.0	82	80	79	77	81	80	78	77	80	78	77	76	78	77	76	75	73
	横方向 (A)	縦方向 (B)	4.0	83	82	81	79	82	81	80	79	81	80	79	78	79	78	77	77	75
Hm	0.45Hm	0.45Hm	5.0	84	83	82	81	83	82	81	80	81	80	80	79	80	79	78	78	76
			7.0	85	84	83	82	84	83	82	81	82	81	81	80	80	80	79	79	77
			10.0	85	84	84	83	84	84	83	83	82	82	82	81	81	80	80	80	78

