

屋内照明器具特性

品番 (品名)	XLGB1408	
光源	LLD4000LCE1 ×1	845.0 l m
管理番号	K0182819 (0) DB 1	
BZ分類	BZ4 / 0.7 / BZ3	

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	81 %	室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.67	0.6	4.9	4.0	3.4	3.0	4.8	4.0	3.4	3.0	4.6	3.9	3.4	3.0	4.5	3.8	3.3	3.0	2.8			
		0.63	0.8	5.8	5.0	4.4	4.0	5.7	4.9	4.4	4.0	5.5	4.8	4.4	4.0	5.3	4.7	4.3	4.0	3.8			
		0.56	1.0	6.4	5.7	5.1	4.7	6.3	5.6	5.1	4.7	6.1	5.5	5.0	4.7	5.9	5.4	5.0	4.7	4.5			
			1.25	6.9	6.2	5.8	5.4	6.8	6.2	5.7	5.4	6.6	6.1	5.7	5.3	6.4	5.9	5.6	5.3	5.1			
下方投影面積		cm ²	1.5	7.2	6.6	6.2	5.8	7.1	6.6	6.1	5.8	6.9	6.4	6.1	5.8	6.7	6.3	6.0	5.7	5.5			
等価発光面積		cm ²	2.0	7.6	7.1	6.8	6.4	7.5	7.1	6.7	6.4	7.3	6.9	6.6	6.3	7.1	6.8	6.5	6.3	6.1			
取付高さ	器具間隔最大限		2.5	7.8	7.5	7.1	6.8	7.7	7.4	7.1	6.8	7.5	7.2	7.0	6.7	7.3	7.1	6.8	6.6	6.5			
	横方向 (A)	縦方向 (B)	3.0	8.0	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.4	7.2	7.0	7.5	7.3	7.1	6.9	6.7			
Hm	1.28Hm	1.28Hm	4.0	8.2	7.9	7.7	7.5	8.1	7.9	7.6	7.4	7.9	7.7	7.5	7.3	7.7	7.5	7.4	7.2	7.0			
			5.0	8.3	8.1	7.9	7.7	8.2	8.0	7.8	7.7	8.0	7.8	7.7	7.6	7.8	7.7	7.6	7.4	7.2			
			7.0	8.5	8.3	8.1	8.0	8.3	8.2	8.1	7.9	8.2	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.5			
			10.0	8.6	8.4	8.3	8.2	8.4	8.3	8.2	8.2	8.3	8.2	8.1	8.0	8.1	8.0	7.9	7.9	7.6			

