

<b>屋内照明器具特性</b>	
品番 (品名)	<b>XLGB1528</b>
光源	LLD4000LCE1 ×1                      845.0 lm
管理番号	K0182819 (0) DB1
BZ分類	BZ4/0.7/BZ3

器具効率	81%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	81%	室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.67	0.6	4.9	4.0	3.4	3.0	4.8	4.0	3.4	3.0	4.6	3.9	3.4	3.0	4.5	3.8	3.3	3.0	2.8
	中	0.63	0.8	5.8	5.0	4.4	4.0	5.7	4.9	4.4	4.0	5.5	4.8	4.4	4.0	5.3	4.7	4.3	4.0	3.8
	否	0.56	1.0	6.4	5.7	5.1	4.7	6.3	5.6	5.1	4.7	6.1	5.5	5.0	4.7	5.9	5.4	5.0	4.7	4.5
			1.25	6.9	6.2	5.8	5.4	6.8	6.2	5.7	5.4	6.6	6.1	5.7	5.3	6.4	5.9	5.6	5.3	5.1
下方投影面積		cm <sup>2</sup>	1.5	7.2	6.6	6.2	5.8	7.1	6.6	6.1	5.8	6.9	6.4	6.1	5.8	6.7	6.3	6.0	5.7	5.5
等価発光面積		cm <sup>2</sup>	2.0	7.6	7.1	6.8	6.4	7.5	7.1	6.7	6.4	7.3	6.9	6.6	6.3	7.1	6.8	6.5	6.3	6.1
取付高さ	器具間隔最大限		2.5	7.8	7.5	7.1	6.8	7.7	7.4	7.1	6.8	7.5	7.2	7.0	6.7	7.3	7.1	6.8	6.6	6.5
	横方向 (A)	縦方向 (B)	3.0	8.0	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.4	7.2	7.0	7.5	7.3	7.1	6.9	6.7
Hm	1.28Hm	1.28Hm	4.0	8.2	7.9	7.7	7.5	8.1	7.9	7.6	7.4	7.9	7.7	7.5	7.3	7.7	7.5	7.4	7.2	7.0
			5.0	8.3	8.1	7.9	7.7	8.2	8.0	7.8	7.7	8.0	7.8	7.7	7.6	7.8	7.7	7.6	7.4	7.2
			7.0	8.5	8.3	8.1	8.0	8.3	8.2	8.1	7.9	8.2	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.5
			10.0	8.6	8.4	8.3	8.2	8.4	8.3	8.2	8.2	8.3	8.2	8.1	8.0	8.1	8.0	7.9	7.9	7.6

