

屋内照明器具特性

品番 (品名)	XLGB1413																			
光源	LLD4000VCE1 ×1 845.0 lm																			
管理番号	K0185514 (0) DR1																			
BZ分類	BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3 / 6.0/BZ2																			
器具効率	67%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%																			
下方光束	67%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.67 0.63 0.56	0.6	4.2	3.4	2.9	2.6	4.1	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.8	3.3	2.9	2.6	2.5	
		0.8	4.9	4.3	3.8	3.5	4.8	4.2	3.8	3.5	4.7	4.1	3.7	3.4	4.5	4.0	3.7	3.4	3.3	
		1.0	5.4	4.8	4.4	4.1	5.3	4.8	4.4	4.1	5.1	4.7	4.3	4.0	5.0	4.6	4.3	4.0	3.9	
		1.25	5.8	5.3	4.9	4.6	5.7	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.4	5.0	4.8	4.5	4.4	
下方投影面積 等価発光面積	c m ² c m ²	1.5	6.1	5.6	5.2	5.0	6.0	5.5	5.2	4.9	5.8	5.4	5.1	4.9	5.6	5.3	5.1	4.9	4.7	
		2.0	6.4	6.0	5.7	5.5	6.3	5.9	5.7	5.4	6.1	5.8	5.6	5.4	6.0	5.7	5.5	5.3	5.2	
		2.5	6.6	6.3	6.0	5.8	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.7	6.1	5.9	5.8	5.6	5.5	
取付 高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.22 H m	1.22 H m	4.0	6.8	6.6	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	5.9
			5.0	6.9	6.8	6.6	6.5	6.9	6.7	6.6	6.4	6.7	6.6	6.4	6.3	6.5	6.4	6.3	6.2	6.1
			7.0	7.0	6.9	6.8	6.7	7.0	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.6	6.6	6.5	6.4	6.2
			10.0	7.1	7.0	7.0	6.9	7.0	7.0	6.9	6.8	6.9	6.8	6.7	6.7	6.7	6.7	6.6	6.6	6.4

